

## Pressure Gauge



Axial

Radial

**PG - P 40 A**



- Two connection types: (1)G1/4" (2)M10x1
- For 40mm gauge, the scale: 0 - 6 bar
- For 50mm gauge, the scale: 0 - 10 bar or 0 - 6 bar
- Back/bottom connection

## Electromagnetic Switch



PS-04A

<b>Rated Voltage</b>	220-240V	110-120V	110-240V
<b>Power Frequency</b>	50/60 Hz		
<b>Max.Power</b>	1.1 kW/1.5 kW	0.55 kW	0.55 kW(110-120V) /1.1 kW(220-240V)
<b>Max. Using Current</b>	10 A		
<b>Start Pressure Setting</b>	1.2 bar / 1.5 bar / 2.2 bar		
<b>Max. Working Pressure</b>	10 bar		
<b>Connection Thread</b>	G1"(Standard) G1 1/4"; G1 1/2"; NPT1"(Optional)		
<b>Protection Rating</b>	IP65		
<b>Max. Working Temperature</b>	55 °C		
<b>Cable</b>	1.6m plug cable 45cm pump connection cable		



PS-04B

<b>Rated Voltage</b>	220-240V	110-120V	110-240V
<b>Power Frequency</b>	50/60 Hz		
<b>Max.Power</b>	1.1 kW	0.55 kW	0.55 kW(110-120V) /1.1 kW(220-240V)
<b>Max. Using Current</b>	10 A		
<b>Start Pressure Setting</b>	1.2 bar / 1.5 bar / 2.2 bar		
<b>Max. Working Pressure</b>	10 bar		
<b>Connection Thread</b>	R1"		
<b>Protection Rating</b>	IP65		
<b>Max. Working Temperature</b>	55 °C		
<b>Cable</b>	1.6m plug cable 45cm pump connection cable		

Optional: Working pressure adjustable



PS-04C

<b>Rated Voltage</b>	220-240V	110-120V	110-240V
<b>Power Frequency</b>	50/60 Hz		
<b>Max.Power</b>	1.1 kW/1.5 kW	0.55 kW	0.55 kW(110-120V) /1.1 kW(220-240V)
<b>Max. Using Current</b>	10 A		
<b>Start Pressure Setting</b>	1.2 bar / 1.5 bar / 2.2 bar		
<b>Max. Working Pressure</b>	10 bar		
<b>Connection Thread</b>	G1"		
<b>Protection Rating</b>	IP65		
<b>Max. Working Temperature</b>	55 °C		
<b>Cable</b>	1.6m plug cable 45cm pump connection cable		



PS-04D

<b>Rated Voltage</b>	220-240V	110-120V	380V
<b>Power Frequency</b>	50/60 Hz		
<b>Max.Power</b>	2.2 kW	1.1 kW	4.0 kW
<b>Max. Using Current</b>	30 A		
<b>Start Pressure Setting</b>	1.2 bar / 1.5 bar / 2.2 bar		
<b>Max. Working Pressure</b>	10 bar		
<b>Connection Thread</b>	G1"(Standard) G1 1/4"; G1 1/2"(Optional)		
<b>Protection Rating</b>	IP65		
<b>Max. Working Temperature</b>	55 °C		
<b>Cable</b>	1.6m plug cable 45cm pump connection cable		